

nMCS **n**otebook PXle **M**easurement & **C**ontrol **S**ystem **HW-1663(G3)**

Built-in ultra-long-life smart lithium battery
Optional high-capacity external smart lithium battery to realize long-term operation of equipment
Compliant with PXle/PXI bus standard specifications
Built-in HOUWU® PXle-9170 controller
Built-in HOUWU® 3U 6-slot PXle Gen3.0 high-speed backplane
One 3U PXle system slot and five 3U PXle/PXI hybrid expansion slots
System slot bandwidth 16GB/s
Each expansion slot has a dedicated bandwidth 8GB/s
Compatible with PXle/PXI modules such as data acquisition, modular instruments aviation bus, FPGA, etc.
Built-in system status monitoring and management software HMCSP
Built-in smart lithium battery monitoring and management software HBSSM
All aluminum-magnesium alloy reinforced compact design
Special impact resistant corners and reinforced silicone handle design
15.6" high-definition industrial display with 1920x1080 resolution
Multi-point capacitive touch screen or resistive touch screen
Industrial touch pad and waterproof silicone keyboard
9V~32V DC power supply wide voltage input (with dedicated 24V power adapter)
Power input with aviation connector design
PXle cage retracted 45mm design
Flexibly customizable IO interface with aviation connector



HW-1663方案

The industry's first high-performance 3U 6-slot PXle ruggedized notebook

HW-1663(G3) is the industry's first 15.6" PXle ruggedized notebook with built-in Intel® Core™ 6th or 9th or 11th Gen i7 Quad-core eight-thread, six-core twelve-thread, or eight-core sixteen-thread CPU, embedded PXle controller, PXle backplane, smart lithium battery, high-definition industrial display and ruggedized chassis. This PXle notebook adopts professional industrial appearance design, all aluminum-magnesium alloy structure reinforced compact design, integrated 15.6" high-definition industrial display, multi-point capacitive touch screen or resistive touch screen, industrial touch pad, waterproof silicone keyboard and smart lithium battery, etc. It has the characteristics of high integration, robustness, portability, and is suitable for various harsh indoor and outdoor environments or complex working conditions where test equipment needs to be portable and mobile.

HW-1663(G3) built in high-performance HOUWU® 3U 6-slot PXle high-speed backplane, based on PCIe Gen3.0 technology, in compliant with PXle/PXI bus standard specifications, with one 3U PXle system slot and five 3U PXle/PXI hybrid expansion slots (compatible with PXle and PXI modules). The system slot bandwidth is 16GB/s, each expansion slot has a dedicated bandwidth 8GB/s, compatible with PXle/PXI modules such as high-speed data acquisition, high-speed digitizer, digital multimeter, aviation bus, FPGA, RF and switch modules. The machine has built-in system status monitoring and management software HMCSP, which can monitor the voltage of each power supply, chassis internal temperature and fan speed in real time, and supports PWM fan speed control. According to the high and low temperature inside the chassis, the fan speed is adaptively adjusted to dissipate heat for the controller and modules. The machine has built-in smart lithium battery monitoring and management software HBSSM, which can monitor all status parameters of the smart lithium battery in real time, including battery voltage, charging and discharging current, real-time power, battery life, charging and discharging times, etc.

HW-1663(G3) makes full use of the characteristics of PXle/PXI bus, such as stability, reliability, good compatibility, solid structure, large data throughput, high performance. According to the different project applications, this measurement & control platform can be built with various PXle/PXI modules to realize the test and measurement of microwave, radio frequency, high-speed digital, signal simulation, prototype validation, voltage, current, temperature, frequency, stress, strain, vibration, shock, audio, video and various aviation bus, etc. Users can quickly build various measurement, test and control system on this portable measurement & control platform, which is suitable for military defense, aerospace, weapons, electronics, ships and other field actual combat applications and scientific experimental research occasions.

SHENZHEN HOUWU TECHNOLOGY CO., LTD.

4th Floor, Building B, Taohuayuan Science and Technology Innovation Park
No. 9 Furong Road, Songgang, Bao'an District, Shenzhen, China

+86-755-29982022

<http://www.houwu.com.cn>

Operating System	Windows® 7 (Option 1, Option 2) Windows® 10 (Option 1, Option 2, Option 3, Option 4, Option 5)
CPU	Intel® Core™ 6 th Gen i7-6822EQ 2.0GHz (8MB Cache, up to 2.8GHz) Quad-Core, Eight-Thread (Option 1) Intel® Core™ 6 th Gen i7-6820EQ 2.8GHz (8MB Cache, up to 3.5GHz) Quad-Core, Eight-Thread (Option 2) Intel® Core™ 9 th Gen i7-9850HL 1.9GHz (9MB Cache, up to 4.1GHz) Six-Core, Twelve-Thread (Option 3) Intel® Core™ 9 th Gen i7-9850HE 2.7GHz (9MB Cache, up to 4.4GHz) Six-Core, Twelve-Thread (Option 4) Intel® Core™ 11 th Gen i7-11850HE 2.6GHz (24MB Cache, up to 4.7GHz) Octa-Core Sixteen-Thread (Option 5)
RAM	16GB DDR4 (upgradeable to 32GB/64GB)
Storage	Original dual solid state drive SSD design: 1, NVMe 500GB SSD x1 (system disk) (upgradeable to 1TB/2TB/4TB) 2, 2.5" SATA3.0 1TB SSD x1 (data disk) (upgradeable to 2TB/4TB/8TB)
Link Configuration	PXle-9170 Controller PCIe Gen3.0 Specification 2 Link: PCIe3.0 x8 + PCIe3.0 x8
LCD	15.6" high-definition industrial display with 1920x1080 resolution
Touch Screen	Multi-point capacitive touch screen / Industrial resistive touch screen (optional)
Backplane	3U 6-slot PXle backplane based on PCIe Gen3.0 technology 1 PXle system slot and 5 PXle/PXI hybrid expansion slots System slot bandwidth 16GB/s, each expansion slot has a dedicated bandwidth 8GB/s
IO	LAN x2, USB3.0 x4, USB2.0 x2, RS232 x1, DP x2, VGA x1, SMB x1, RESET x1, LED x4 PXle cage retracts 45mm and the aviation connector IO adapter panel area is 285mm x 86mm.
Keyboard	Waterproof silicone keyboard
Aviation Connector	Users can flexibly customize IO interfaces with aviation connectors for PXle/PXI modules
Heat Dissipation	The fan supports PWM operation mode, adaptive speed regulation, active heat dissipation, and complies with PXle/PXI bus standard specifications.
Internal Battery	Smart lithium battery 150WH (default)
External Battery	Smart lithium battery 300WH (optional)
Power Supply	9V~32V DC wide voltage input, aviation connector design With dedicated power adapter: input AC 100V~240V, output DC 24V Rated load power 200W
Environment	Operating temperature: 0°C ~ 50°C (normal level) Operating temperature: -10°C ~ 55°C (industrial level) Storage temperature: -40°C ~ 70°C Relative humidity: 5% ~ 95% (no condensation)
Shock Resistance	30G peak, half-sine, 11ms pulse
Vibration Resistance	2.4Grms@5~500Hz (1 hour each in X, Y, Z directions)
Dimension	401 x 315 x 149 mm (excluding corners and handles)

Weight	11.7KG (including HOUWU® PXIe-9170 controller, 150WH smart lithium battery)
Packaging	Customized aviation trolley case
Category	nMCS, notebook PXIe Measurement & Control System

Note: Due to regular product upgrades, for more updated and accurate specifications and configuration information, please contact HOUWU TECHNOLOGY at +86-755-29982022.