

pMCS portable PXIe Measurement & Control System

HW-1693

Compliant with PXIe/PXI bus standard specifications
HW-1693(G3) and HW-1693(G2) are available for selection

HW-1693(G3)

Built-in HOUWU® PXIe-9180 controller
Built-in HOUWU® 3U 9-slot PXIe Gen3.0 high-speed backplane
One 3U PXIe system slot, seven 3U PXIe/PXI hybrid expansion slots and one 3U PXIe timing slot
System slot bandwidth 24GB/s, each expansion slot has a dedicated bandwidth 8GB/s

HW-1693(G2)

Built-in HOUWU® PXIe-9170 controller
Built-in HOUWU® 3U 9-slot PXIe Gen2.0 backplane
One 3U PXIe system slot and eight 3U PXIe/PXI hybrid expansion slots
System slot bandwidth 8GB/s, three 4GB/s expansion slots and five 2GB/s expansion slots

Compatible with PXIe/PXI modules such as data acquisition, modular instrument, aviation bus, FPGA, etc.

All aluminum magnesium alloy reinforced compact design

Special impact resistant corners and reinforced silicone handle design

15.6" high-definition industrial display with 1920x1080 resolution

Industrial resistive touch screen, industrial touch pad and waterproof silicone keyboard

AC power input with aviation connector design

PXIe cage retracted 140mm design

Flexibly customizable IO interface with aviation connector



HW-1693方案

The industry's first domestic high-performance 3U 9-slot PXIe ruggedized portable

HW-1693 is the industry's first 15.6" ruggedized portable with built-in embedded PXIe controller, PXIe backplane, high-definition industrial displays and ruggedized chassis. This platform adopts professional industrial appearance design, all aluminum-magnesium alloy structure reinforced compact design, integrated 15.6" high-definition industrial display, industrial resistive touch screen, industrial touch pad, waterproof silicone keyboard and control power supplies. It has the characteristics of high integration, robustness, portability, and is suitable for various harsh indoor and outdoor environments or complex working conditions where test equipment needs to be portable and mobile.

HW-1693(G3)

Built-in HOUWU® high-performance 3U 9-slot PXIe high-speed backplane, based on PCIe Gen3.0 technology, compliant with PXIe/PXI bus standard specifications, with one PXIe system slot, seven PXIe/PXI hybrid expansion slots (compatible with PXIe and PXI modules) and one PXIe timing slot. The system slot bandwidth is 24GB/s, each expansion slot has a dedicated bandwidth 8GB/s.

HW-1693(G2)

Built-in HOUWU® high-performance 3U 9-slot PXIe backplane, based on PCIe Gen2.0 technology, compliant with PXIe/PXI bus standard specification, with one PXIe system slot and eight PXIe/PXI hybrid expansion slots (compatible with PXIe and PXI modules). The system slot bandwidth is 8GB/s, providing three dedicated 4GB/s bandwidth PXIe/PXI hybrid expansion slots and five dedicated 2GB/s bandwidth PXIe/PXI hybrid expansion slots.

SHENZHEN HOUWU TECHNOLOGY CO., LTD.

4th Floor, Building B, Taohuayuan Science and Technology Innovation Park

No. 9 Furong Road, Songgang, Bao'an District, Shenzhen, China

+86-755-29982022

<http://www.houwu.com.cn>

HW-1693 is compatible with PXIe/PXI modules such as high-speed data acquisition, high-speed digitizer, digital multimeter, aviation bus, FPGA, RF and switch modules. This PXIe portable platform supports PWM fan speed control, according to the internal temperature of the chassis fan adaptive speed adjustment to the controller and module cooling.

HW-1693 makes full use of the characteristics of PXIe/PXI bus, such as stability, reliability, good compatibility, solid structure, large data throughput, high performance. According to the different project applications, this PXIe portable can be built with various PXIe/PXI modules to realize the test and measurement of microwave, radio frequency, high-speed digital, signal simulation, prototype verification, voltage, current, temperature, frequency, stress, strain, vibration, shock, audio, video and various aviation bus, etc. Users can quickly build various measurement, test and control system on this portable measurement & control platform, which is suitable for military defense, aerospace, weapons, electronics, ships and other field actual combat applications and scientific experimental research occasions.

Operating System	Windows® 7 Windows® 10
CPU	HW-1693(G3) Intel® Xeon® Processor D-1548 2.0GHz (12M Cache, up to 2.6 GHz) Octa-Core, Sixteen-Threads HW-1693(G2) Intel® Core™ 6 th Gen i7-6822EQ 2.0GHz (8MB Cache, up to 2.8GHz) Quad-Core, Eight-Thread (Option 1) Intel® Core™ 6 th Gen i7-6820EQ 2.8GHz (8MB Cache, up to 3.5GHz) Quad-Core, Eight-Thread (Option 2) Intel® Core™ 9 th Gen i7-9850HL 1.9GHz (9MB Cache, up to 4.1GHz) Six-Core, Twelve-Thread (Option 3) Intel® Core™ 9 th Gen i7-9850HE 2.7GHz (9MB Cache, up to 4.4GHz) Six-Core, Twelve-Thread (Option 4) Intel® Core™ 11 th Gen i7-11850HE 2.6GHz (24MB Cache, up to 4.7GHz) Octa-Core Sixteen-Thread (Option 5)
RAM	HW-1693(G3) 16GB DDR4 (upgradeable to 32GB/48GB) HW-1693(G2) 16GB DDR4 (upgradeable to 32GB/64GB)
Storage	HW-1693(G3) SATA 1TB SSD (upgradeable to 2TB) HW-1693(G2) Original dual solid state drive SSD design: 1, NVMe 250GB SSD x1 (system disk) (upgradeable to 1TB/2TB/4TB) 2, SATA3.0 1TB SSD x1 (data disk) (upgradeable to 2TB/4TB/8TB)
Link Configuration	HW-1693(G3) with PXIe-9180 Controller PCIe Gen3.0 Specification 2 Link mode: PCIe3.0 x16 + PCIe3.0 x8 HW-1693(G2) with PXIe-9170 Controller PCIe Gen3.0 Specification 2 Link mode: PCIe3.0 x8 + PCIe3.0 x8
LCD	15.6" high-definition industrial display with 1920x1080 resolution
Touch Screen	Industrial resistive touch screen
Backplane	HW-1693(G3) 3U 9-slot PXIe backplane based on PCIe Gen3.0 technology 1 PXIe system slot, 7 PXIe/PXI hybrid expansion slots and 1 PXIe timing slot System slot bandwidth 24GB/s, each expansion slot has a dedicated bandwidth 8GB/s HW-1693(G2) 3U 9-slot PXIe backplane based on PCIe Gen2.0 technology 1 PXIe system slot and 8 PXIe/PXI hybrid expansion slots System slot bandwidth 8GB/s, slots 2 through 4 bandwidth 4GB/s, slots 5 through 9 bandwidth 2GB/s

IO	HW-1693(G3) LAN x2, USB3.0 x4, USB2.0 x2, RS232 x2, DP x2, SMB x1, LED x2
	HW-1693(G2) LAN x2, USB3.0 x4, USB2.0 x2, RS232 x1, DP x2, VGA x1, SMB x1, RESET x1, LED x4
	The PXIe cage retracts 140mm and the aviation connector IO adapter panel area is 239mm x 147mm
Key board	Waterproof Silicone Keyboard
Aviation Connector	Users can flexibly customize IO interfaces with aviation connectors for PXIe/PXI modules
Heat Dissipation	The fan supports PWM operation mode, adaptive speed regulation, active heat dissipation, and complies with PXIe/PXI bus standard specifications.
Power Supply	400W, industrial grade, AC input, 90VAC~264VAC, 47Hz~63Hz, aviation connector design
Environment	Operating temperature: 0°C ~ 50°C (normal level) Operating Temperature: -10°C ~ 55°C (industrial level) Storage Temperature: -40°C ~ 70°C Relative Humidity: 5% ~ 95% (no condensation)
Shock Resistance	30G peak, half-sine, 11ms pulse
Vibration Resistance	2.4Grms@5~500Hz (1 hour each in X, Y, Z directions)
Dimension	423 x 320 x 226 mm (excluding corners and handles)
Weight	HW-1693(G3) 14.9KG (including HOUWU® PXIe-9180 controller)
	HW-1693(G2) 13.5KG (including HOUWU® PXIe-9170 controller)
Packaging	Customized aviation trolley case
Category	pMCS, portable PXIe Measurement & Control System

Note: Due to regular product upgrades, for more updated and accurate specifications and configuration information, please contact HOUWU TECHNOLOGY at +86-755-29982022.